DR SYSTEM



EHS 1210



EHS 1210 provides excellent waterproof protection for the detector.

Wireless charging system enables rapid charging anytime, anywhere.

It uses software that is designed for your convenience and has a variety of features. Provide the best high-definition image.









SMART PORTABILITY HIGH RESOLUTION IMAGE

TRUEVIEW ART

STRONG DURABILITY





WATERPROOF AND DUSTPROOF

EHS 1210 protects the detector with excellent waterproofing. Protect the detector from debris or liquids that may occur during filming.



WIRELESS CHARGING

Wireless charging system WPCS enables rapid charging anytime, anywhere. Use the detector in wireless mode 24 hours a day.






ECONSOLE1

Designed and equipped for your convenience Use software ECONSOLE1.

TRUVIEW ART

TRUVIEW ART provides enhanced detection capabilities. Provide the best high-definition image.





SPECITICATIONS

Model	EHS1210
Sensor Type	Csl or GOS
Active Area	291(W) x 233(H) mm
Resolution	3840 x 3072
Pixel size	World Best76μm (High Resolution)
Spartial Resolution	6.5lp/mm
Dynamic Range	16 bit
X-ray Range	Up to 330 kVp
IP Testing	IP67
X-ray Window Time	Up to 3 Min
Operationg Temp.	-15°C< Operating < 50°C
External Dimensions	327(H) x 362(W) x 21.5(D)mm
Weight	3.2 kg (with Radiation Protection Sheild)
Communication Protocols	1G LAN & Wi-fi

